

Tender Sample Text

**BLICKS Professional**  
**Gabion Fence**

**BLICKS Professional Gabion Fence**

To provide and install **BLICKS Professional** Gabion Fence with a filling of hard and durable, sufficiently strong frost, weather and pressure resistant stone material.

Wire mesh baskets, made of electro-spot-welded, steel-wire mesh-grids with a tensile strength of  $\geq 450 \text{ N/mm}^2$ .

Sizes of modules (standard): Length:100cm/200cm (basic module or extension module)  
Width: 23cm/30cm  
Height:60cm/100cm/120cm/140cm/160cm/180cm/200cm

(Shortening and cutting of fence modules is possible in accordance to mesh sizes)

<u>module size:</u>	(LxWxH in cm)	_____ cm	
<b><u>mesh size:</u></b>	5x20cm	5x10cm	2,5x10cm
<b><u>wire size:</u></b>	$\varnothing 6,0\text{mm}$	$\varnothing 4,5\text{mm}$ vertical $\varnothing 7,0\text{mm}$ horizontal	$\varnothing 3,5\text{mm}$ vertical $\varnothing 6,0\text{mm}$ horizontal
<b><u>Staying rod:</u></b>	wire- $\varnothing 4,5\text{mm}$		
<b><u>Fixing hooks:</u></b>	wire- $\varnothing 4,5\text{mm}$		
<b><u>Fence post:</u></b>	$\varnothing 60,3\text{mm}$		
<b><u>Protection cap (post):</u></b>	$\varnothing 60,3\text{mm}$		

All items are made of Zn95%/Al 5% wire – with a corrosion resistance of min. 3.000 h salt spray testing, according to DIN EN ISO 9227:2006-10 NSS, with modified parameters as a minimum thickness of  $350\text{g/m}^2$  and a tensile strength of  $\text{min.}450 \text{ N/mm}^2$ .

Manufacturer DIN EN ISO 9001- certified.

To install component parts and to fill with stone materials without voids according assembly instructions of supplier at construction site.

Filling: Sufficiently hard, durable, strong frost, weather and pressure resistant stone material. The grain size has to be bigger than the mesh size.

Total Height: up to \_\_\_\_\_ m  
consisting of \_\_\_\_\_ pieces (LxWxH)/ basic modules  
\_\_\_\_\_ pieces (LxWxH)/ extension modules

Proof of delivery: Rothfuss Best Gabion GmbH & Co. KG  
Dr.-Oetker-Straße 30  
54516 Wittlich  
kontakt@rbg.eu  
Tel.: 06571/95233-0  
Fax: 06571/95233-55

or similar