

Tender Sample Text

DELTA GREEN

DELTA GREEN Facing Element

To provide and install **DELTA GREEN** facing element for steep slope protection with a gradient angle of 60°/70°.

Steep slope protection with a gradient angle of 60°/70° according to “**DELTA GREEN**” system, consisting of:

- Front grids 300x73cm, wire-Ø 5,0mm, mesh size 10x10cm
- Bottom grids 300x70cm, wire-Ø 4,5mm, mesh size 10x10cm
- Locking rods wire-Ø 6,0mm
- Staying rods wire-Ø 6,0mm

All items are made of Zn95%/Al 5% wire – with a corrosion resistance of min. 3.000 h salt spray testing, according to DIN EN ISO 9227:2006-10 NSS, with modified parameters as a minimum thickness of 350g/m² and a tensile strength of min.450 N/mm².

Manufacturer DIN EN ISO 9001- certified.

Connection of grids with curved and welded eyelet and locking rod.

To provide and install reinforcement grids with required tensile strength, anchorage length, distance of layers according to statics.

To connect geogrids to steel grid unit according to static requirements.

Corresponding earthwork and greening will be remunerated separately.

All proofs have to be provided before acceptance of tender.

Payment shall be measured and paid for the unit bid price per m² (slope area)
or apiece (elements)

To provide and install component parts of **DELTA GREEN** system according assembly instructions of supplier at construction site.

Slope with a gradient angle of 60°/70°

_____ m²/ € per m² _____ or _____ pcs. / € apiece.

Proof of delivery: Rothfuss Best Gabion GmbH & Co. KG
Dr.-Oetker-Straße 30
54516 Wittlich
kontakt@rbg.eu
Tel.: 06571/95233-0
Fax: 06571/95233-55

or similar