

Tender Sample Text

GTP

To provide pre-filled and compacted wire mesh baskets and to install on existing gravel or concrete base course.

Rock-fill has to be of hard and durable, sufficiently strong frost, weather and pressure resistant stone material. Wire mesh baskets, made of electro-spot-welded, steel-wire mesh-grids.

Basket sizes (standard): Length: 50cm/100cm/150cm/200cm
Width: 50cm/100cm
Height: 50cm/100cm

Basket size: (LxWxH in cm) _____ cm

Mesh sizes: 5x20cm
10x20cm (cover grid)

Wire size: Ø 6,0mm
Ø 4,5mm (cover grid)

Stay rod: wire-Ø 5,0mm

All items are made of Zn95%/Al 5% wire – with a corrosion resistance of min. 3.000 h salt spray testing, according to DIN EN ISO 9227-NSS, with modified parameters as a minimum thickness of 350g/m² and a tensile strength of min.450 N/mm².

Manufacturer DIN EN ISO 9001- certified, as well as user of the Quality Mark GABIONEN according to Quality Assurance Gabions and Gabion Structures RAL-GZ 612 and holder of an ETA (European Technical Assessment).

Connection of grids by means of folded side and bottom ends.
The cover grid is connected with wire clamps.

Filling: Sufficiently hard, durable, strong frost, weather and pressure resistant stone material. The grain size has to be bigger than the mesh size.

Proof of delivery
for steel component parts: Rothfuss Best Gabion GmbH & Co. KG
Dr.-Oetker-Straße 30
D-54516 Wittlich
kontakt@rbg.eu
Tel.: +49 (0)6571/95233-0
Fax: +49 (0)6571/95233-55

or similar